

Safety Data Sheet: California Green, Floor Stripper

SECTION 1: Identification

Product identifier

Product name California Green, Floor Stripper

Product number 187600.2000

Recommended use of the chemical and restrictions on use

Floor stripper

Supplier's details

Name California Prison Industry Authority
Address CSP-Los Angeles County
44750 60th Street West
Lancaster, CA 93536

Telephone (661) 729-2000 Ext. #7930

Emergency phone number(s)

1 (800) 424-9300

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Eye damage/irritation, Cat. 1
- Skin corrosion/irritation, Cat. 1B

GHS label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H314
H318

Causes severe skin burns and eye damage
Causes serious eye damage

Precautionary statement(s)

P260
P264
P280

Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331
P303+P361+P353

P304+P340
P305+P351+P338

P310
P363
P405
P501

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Mixtures

Hazardous components

1. Dipropylene glycol monomethyl ether

Concentration 5 – 10 % (weight)
CAS no. 34590-94-8

2. Dipropylene glycol butoxy ether

Concentration 5 – 10 % (weight)
CAS no. 29911-28-2

3. Ethanolamine

Concentration 3 – 7 % (weight)
CAS no. 141-43-5

4. Proprietary surfactant

Concentration 2 – 5 % (weight)

Trade secret statement (OSHA 1910.1200(i))

Exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
If inhaled	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include burning pain in the nose and throat, coughing, wheezing, shortness of breath and pulmonary edema.
In case of skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower for at least 15 minutes. Call a poison center or doctor if irritation develops or persists. Wash contaminated clothing before reuse.

Acute and delayed symptoms and effects: Causes severe skin burns. Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

In case of eye contact

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

Acute and delayed symptoms and effects: Causes serious eye damage. Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

If swallowed

Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.

Acute and delayed symptoms and effects: Harmful if swallowed. Causes burns to nose, mouth, throat, and digestive tract. Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea, blood in the feces and/or vomitus may also be seen.

Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Indication of immediate medical attention and special treatment needed, if necessary

No data available.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical

Carbon oxides. Sulfur oxides. Nitrogen oxides. Sodium oxides

Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear respiratory protection if necessary. Do not breathe dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

Environmental precautions

Do not let concentrated product enter drains.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of in accordance with local and national regulations. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**Precautions for safe handling**

Do not swallow. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

Conditions for safe storage, including any incompatibilities

Store in a well ventilated place. Keep container tightly closed. Store between the following temperatures: 40 and 120 Fahrenheit and out of direct sunlight and away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of reach of children.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection**Control parameters****CAS: 141-43-5**

Ethanolamine

ACGIH (USA): 3 ppm, (ST) 6 ppm TLV® inhalation; Cal/OSHA: 3 ppm, (ST) 6 ppm PEL inhalation; NIOSH: 3 ppm, (ST) 6 ppm REL inhalation; OSHA: 3 ppm PEL inhalation; 6 mg/m³ PEL inhalation

CAS: 34590-94-8

Dipropylene glycol methyl ether

ACGIH (USA): 100 ppm, (ST) 150 ppm TLV® inhalation; Cal/OSHA: 100 ppm, (ST) 150 ppm PEL inhalation; NIOSH: 100 ppm, (ST) 150 ppm REL inhalation; OSHA: 100 ppm PEL inhalation; 600 mg/m³ PEL inhalation

Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

Individual protection measures, such as personal protective equipment (PPE)**Eye/face protection**

Tightly fitting safety goggles. Faceshield (8-inch minimum) if there is a splash hazard. Use equipment for eye protection that meets the standards referenced by OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment. Eyewash stations and/or safety showers may be required when working with the concentrated product.

Skin protection

Wear protective gloves (rubber, chemical resistant). Consult manufacturer specifications for further information.

Body protection

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator with particulate filter, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

Thermal hazards

No data available.

Environmental exposure controls

Do not let concentrated product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Clear thin liquid
Odor	Fresh
Odor threshold	Amber
pH	> 10.5
Melting point/freezing point	No data available.
Initial boiling point and boiling range	No data available.
Flash point	No data available.
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Upper/lower flammability limits	No data available.
Upper/lower explosive limits	No data available.
Vapor pressure	No data available.
Vapor density	No data available.
Relative density	1.018 (Water = 1)
Solubility(ies)	Soluble in water.
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidizing properties	No data available.

SECTION 10: Stability and reactivity

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under normal storage conditions.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids.

Hazardous decomposition products

No data available.

SECTION 11: Toxicological information**Information on toxicological effects****Acute toxicity**

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Product:

ATE (oral): could not calculate

ATE (dermal): could not calculate

ATE (inhalation, gaseous) of mixture: 75749.48 ppmv

Component Toxicity:

Dipropylene glycol butoxy ether:

LD50 Oral - Rat - 4,000 mg/kg

LD50 Skin - Rat - 2,000 mg/kg

Dipropylene glycol monomethyl ether:

LD50 Oral - Rat - 5,152 mg/kg

LD50 Skin - Rabbit - 9510 mg/kg

Ethanolamine:

LD50 Oral - Rat - 1,089 mg/kg

LD50 Skin - Rat - 1,015 mg/kg

Proprietary surfactant:

LD50 Oral - Rat - > 2,000 mg/kg

Symptoms (including delayed and immediate effects):**Inhalation**

May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion

Harmful if swallowed. Causes burns to nose, mouth, throat, and digestive tract. Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea, blood in the feces and/or vomitus may also be seen.

Skin corrosion/irritation

Causes severe skin burns. Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction

Serious eye damage/irritation

Causes serious eye damage. Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Respiratory or skin sensitization

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

SECTION 12: Ecological information**Toxicity**

No data available on product

Components:

Dipropylene glycol butoxy ether:

LC50 - *Daphnia magna* (water flea) - >1,000 mg/l - 48 h

LC50 - *Poecilia reticulata* (guppy) - 841 mg/l - 96 h

Dipropylene glycol monomethyl ether:

LC50 - *Pimephales promelas* (fathead minnow) - > 10,000 mg/l - 96 h

LC50 - *Daphnia magna* (water flea) - 1,919 mg/l - 48 h

Ethanolamine

LC50 - *Cyprinus carpio* (Carp) - 150 mg/l - 96 h

EC50 - *Daphnia magna* (water flea) - 65 mg/l - 48 h

EC50 - *Selenastrum capricornutum* (green algae) - 2.8 mg/l - 72 h

EC50 - *Pseudomonas putida* - 110 mg/l - 17 h

Proprietary surfactant

LC50 - *Daphnia magna* (water flea) - > 100 mg/l - 48 h

LC50 - *Oncorhynchus mykiss* (rainbow trout) - > 100 mg/l - 96 h

EC50 - *Scenedesmus quadricauda* (Green algae) - > 100 mg/l - 72 h

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

No data available.

SECTION 13: Disposal considerations**Disposal of the product**

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Disposal of contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**DOT (US)**

UN Number: UN2491

Class: 8

Packing Group: III

Proper Shipping Name: Ethanolamine Solution

SECTION 15: Regulatory information**Safety, health and environmental regulations specific for the product in question****SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard

Massachusetts Right To Know Components

Dipropylene glycol monomethyl ether

CAS number: 34590-94-8

Pennsylvania Right To Know Components

Dipropylene glycol monomethyl ether

CAS number: 34590-94-8

Di(propylene glycol) butyl ether

CAS: 29911-28-2

Safety Data Sheet

California Green, Floor Stripper

Chemical name: Ethanol, 2-amino-
CAS number: 141-43-5

New Jersey Right To Know Components

Dipropylene glycol monomethyl ether
CAS number: 34590-94-8

Di(propylene glycol) butyl ether
CAS: 29911-28-2

Ethanolamine
CAS number: 141-43-5

California Prop. 65 Components



WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall California Prison Industry Authority be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if California Prison Industry Authority has been advised of the possibility of such damages.